

Traffic Tally[®] 2 (TT-2)



1 Unpack Counter

If your vehicle traffic is consistently at 10 mph (16kmh) or slower, we advise you to consider a “Slow Speed Modification” to the TT2 at no additional cost to you.

- 1) Layout and secure road tube on roadway
- 2) Connect road tube to counter
- 3) Swipe the magnet across the faceplate at the magnet symbol of your TT-2 counter to turn it on.
- 4) To erase old data, swipe the magnet across the red dot on the side of the counter at ANY time while the LCD is on.

To view the data simply swipe the magnet across the front to view the total count number.

Warning: Do not touch the magnet near the red dot on the side of your TT-2, 4, or 6 counters while the display is on unless you want ALL of your data deleted.

2 Items Needed for Field Setup

- TT-2 unit
- Lock
- Chain, for securing unit to anchored object
- Magnet, for TT-2 operation
- Road Tube, 30 feet minimum
- Figure eight or any other road tube grip (2)
- Road nails or spikes (2)

3 Installation Equipment

- Gloves
- Hammer, large head is recommended.
- Safety vest, orange or yellow is recommended.
- Traffic spotter, to act as a lookout and warn vehicle traffic.

Please refer to the “General Guidelines for Road Tube Installation” for more information.

To download this document, visit our website: <http://diamondtraffic.com> or contact our sales or support team at: 541.782.3903.

